



NovoTouch

BK2 series 65" 75" 86"

a 4K UHD Touch Display



Key Features



4K-UHD Resolution

The BK2 series features display size with 4K Ultra-HD (3,840 × 2,160)



Interactive IR Touch Technology

The BK2 series supports 40-point interactive touch capability



Wireless Presentation

Built in NovoConnect for cable free presentation




Backlit D-LED Technology

Brighter picture with a wide viewing angle of 178°



Eye Protection Technology

The BK2 series is TÜV Rheinland Certified which can protect your eyes with low Blue Light & Flicker Free for the best viewing experience.



Product Specification |

Model name		BK652i	BK752i	BK862i
Display	Type/Technology	Backlit D-LED (ADS Panel)		
	Panel Size	65"	75"	86"
	Brightness (Typ)	400cd/m2		
	Contrast Ratio (Typ)	1,200:1		
	Native Resolution	4K Ultra-HD (3840 x 2160)		
	Viewing Angle (H/V)	178°/178°		
	Aspect Ratio	16:9		
	Response Time (MS)	8ms (Typ)		
	Refresh Rate (Hz)	60Hz		
	Estimated Life Time (Typ)	30,000 hours (Min)		
	Display Color (Bit)	1.07 billion (10-bit)		
Installation Orientation	Landscape			
Interactivity	Technology	Infrared Touch		
	Touch Points	Writing	10 Point (Standard)	
		Touch	20 Point (Standard)	
	Accuracy	±1mm (Over 90% area)		
	Response Time	<10ms		
	Touch Resolution	32,768 x 32,768		
	Surface Protection	3mm Anti-Glare Thick Toughened Glass (Level 7H on Mohs Scale of Mineral Hardness)		
Touch Tools	Finger, Stylus, Glove, Opaque Objects			
Operating System	System Version	Android™ v13.0		
	CPU	Multi-Core High-Performance ARM®CPU		
	GPU	Mali™ G52		
	RAM	4GB DDR4		
	Internal Storage	32GB (eMMC Flash) (About 25GB User Availability)		
Connectivity	Input	Display	HDMI v2.0 (x3) Side, HDMI v2.0 (x1) Front	
		Audio	Mic(3.5mm)(x1)	
	Output	Display	HDMI-Out v2.0 (x1) (up to 4K@60Hz)	
		Audio	Line-Out (3.5mm) (x1), SPDIF-Out (x1)	
	Internet	LAN (RJ45) (x2)		
	Control	RS232-In (x1)		
	Wireless	WiFi	IEEE802.11ax (2.4GHz/5GHz)	
		Bluetooth	BT 5.2	
		I/R Receiver	Front (x1) (±25° Angle, >8m Distance)	
	USB-A	Front	USB 3.0 (x2)	
		Side	USB 3.0 (x2), USB 2.0 (x1)	
	USB-B	Front	USB Type B (x1) (For Touch Port)	
		Side	USB Type B (x1) (For Touch Port)	
USB-C	Front	USB-C (x1) (15W charging & display input)		
Expansion	Windows Module (Option)	Standard Intel 80pin OPS (Option)		
	Speakers	18W (x2) (Stereo)		
Power	Power Supply (Internal)	AC 100 - 240V, 50/60Hz (4.5A)		
	Consumption	≤300W	≤360W	≤450W
	Standby Mode	≤0.5W (Standby)		
Physical Characteristics	VESA Mounting (FPMPMI)	600x400mm, 4-M8x25mm	800x400mm, 4-M8x25mm	
	Mini PC VESA Mount	100 x 100mm		
	Dimension (L x H x D)	1,484.5 x 90 x 908 mm	1,705.7 x 90.2 x 1032.3 mm	1,953.0 x 90.2 x 1172.3 mm
	Weight	39kg (85lbs)	50.8kg (111lbs)	63kg (138lbs)
Accessories	Standard	AC Power Cord, Stylus (x2), Remote Control (W/Batteries), Wall Mount Kit, HDMI Cable(3M), Touch Cable(3M), WiFi Antenna(x3), Documentation Kit		